

## DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011  
and the Delegated Regulation (EU) No 574/2014

Product name:

**MEMEASY MALER-ACRYL**

DoP-No 15651- 1-14-98

1. Unequivocal classification of the product type:

**EN 15651-1:2012: F Ext-Int 7,5P**

2. Intended use:

**Joint sealant for indoor and outdoor facades**

3. Manufacturer:

**MEM Bauchemie, Am Emsdeich 52, DE-26789 Leer (Ostfriesland)**

4. Systems of assessment and verification of the constancy of performance:

**System 3 plus 3**

5. Harmonized Standards (hENs):

**EN 15651-1:2012**

6. Notified Body involved:

**A notified testing laboratory, the GINGER CEBTP,  
NB 0074, has performed the determination of the product-type  
and the reaction-to-fire class on the basis of Initial Type Testing  
(ITT) under system 3 and has issued  
corresponding test and classification reports.**

7. European Technical Assessment (ETA):

**not relevant**

Notified Body:

**not relevant**

## 8. Declared performance

Conditioning: procedure A

Substrates: mortar M2 and aluminum, without primer

Essential Product Features	Performance	Harmonized Technical Specification
Reaction to fire (EN 13501-1)	Class E	EN 15651-1:2012
Release of dangerous substances	NPD	
Resistance to flow (EN ISO 7390)	< 3 mm	
Loss of volume (EN ISO 10563)	< 25 %	
Adhesion/elongation after immersion in water (EN ISO 10591)	Passed (NF), Elongation at break > 25 %	
Adhesion/cohesion at constant temperature (EN ISO 9046)	Passed (NF)	
Elongation at break (EN ISO 8339)	> 25 % at 23 °C	
Durability	Passed (NF)	

9. The performance of the a. m product is in conformity with the performance declared in section 8. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer as identified in section 3.

**Signed for and on behalf of MEM Bauchemie GmbH by Company Management**

Leer, March 17, 2015

Managing Director (MD)

